

HDW-120 T5

Powered by:

DOOSAN D1146T

118 kVA - 50 Hz



Generating Set Performance		50 Hz	
SERVICE		Continuous Service	Intermittent Service
Rated output	kVA	118	130
Active power output *	kW	95	104
Rated speed	r.p.m.	1.500	
Standard Voltage	V	400	
Voltage available	V	400/230 - 230/132 - 230	

Performance data refers to Standard Reference Conditions of ISO 8528 : + 25 °C , 100 m ALT, relative humidity 30 %

During running-in period the output increases by approx. 5 % which is taken into consideration at delivery.

Power reduction acc. to DIN ISO 3046. Standard values: Above 100 m ALT approx. 1 % per 100 m. Above 25 °C (77 °F) approx. 4 % per 10 °C (50 °F).

* Considering cos phi= 0,8

Prime Mover Performance		1.500 r.p.m.	
SERVICE		Continuous Service	Intermittent Service
Rated output	kW	107	118
Manufacturer		DOOSAN	
Engine model		D1146T	
4 stroke Diesel Engine - Injection type		DIRECT	
Aspiration type		TURBO CHARGED & INTERCOOLED	
Cylinders, number and arrangement		6 - L	
Bore x stroke	mm	111 x 139	
Total displacement	L	8,071	
Cooling system		WATER	
Lube oil specifications		SAE 15W 40 - API CD/CE	
Compression ratio		16,8 : 1	
Specific fuel consumption	L/h	25,9 - 19,5 - 13,6 - 8,2	
Specific oil consumption (at full load)	%	--	
Lube oil maximum capacity	L	15,5	
Lube oil minimum capacity	L	12	
Speed governor	Type	ELECTRONIC	
Steady state frequency at constant load	Type	<1,5*	
Governor class according to ISO 8528		G2	
Air filter		DRY	

(ICFN) : ISO-STANDARD POWER (10% overload permissible) and ISO-STANDARD FUEL STOP POWER (no overload permissible) according to DIN ISO 3046.

For constant speed and constant load.

(IFN) : ISO BRAKE FUEL STOP NET POWER for intermittent load acc. to DIN ISO 3046.

Performance data refers to Standard Reference Conditions of DIN ISO 3046: + 25 °C , 100 m ALT, relative humidity 30 % During running-in period the output increases by approx. 5 % which is taken into consideration at delivery. Power reduction acc. to DIN ISO 3046. Standard values: Above 100 m ALT approx. 1 % per 100 m. Above 25 °C (77 °F) approx. 4 % per 10 °C (50 °F).


Synchronous Generator *		
Pôles	N°	4
Winding connections (standard)		Star - serie
Frame mounting		SAE1 / 14"
Insulation	class	H
Enclosure (according to IEC-34-5)		IP 23
Exciter system		3 + N
Voltage regulator		A.V.R. (electronic)
Steady voltage precision		within ± 1,5% from no load to full loading with cosφ=0,8+1
Maintained short circuit current		3 In

*Alternator used by HIMOINSA Gensets meet the requirements of following Standard: IEC 34-1; CEI 2-3; ; VDE 0530; BS 4999-5000:NF 51-100,11

Generating Set Installation Data		1.500 r.p.m.
EXHAUST SYSTEM		
Max. exhaust temperature at full load	° C	470
	° F	878
Exhaust outlet diameter (Open skid - Soundproofed)	mm	--
Exhaust gas flow	m ³ /m	25,7
Heat rejected to coolant	kcal/kWh	--
Max. permissible restrictions	mmH ² O	600
AIR REQUIREMENT		
Cooling air flow	m ³ /s	--
Cooling air flow alternator	m ³ /m	--
Total cooling air flow (engine, alternator, combustion)	m ³ /m	--
ELECTRIC STARTING SYSTEM		
Starting motor output	kW	4,5
	CV	6,12
Minimum recommended battery capacity	Ah	100
Auxiliary voltage	Vcc.	24
LIQUID CAPACITY		
Lube oil system including sump, filters, etc.	L	16,5
Cooling system capacity	L	--
Antifreeze recommended percentage	%	--
FUEL TANK		
Fuel tank capacity Open Skid Genset	L	250
Autonomy (100%-75%-50%-25%)	h	9,65 - 12,82 - 18,38 - 30,49
Fuel tank capacity Soundproofed	L	225
Autonomy (100%-75%-50%-25%)	h	8,69 - 11,54 - 16,54 - 27,44


Generating Set transport data		
WEIGHT AND DIMENSIONS OPEN SKID GENSET		
Length	m - ft	2,90 - 9,51 (a)
Width	m - ft	0,90 - 2,95
Height	m - ft	Consult.
Shipping volume seaworthy (Standard supplier)	m ³ - ft ³	Consult.
Dry weight (with standard accessories)	kg - lb	1.750 - 3.850
WEIGHT AND DIMENSIONS SOUNDPROOFED GENSET		
Length	m - ft	3,30 - 10,82
Width	m - ft	1,20 - 3,93
Height	m - ft	1,924 - 6,31
Shipping volume seaworthy (Standard supplier)	m ³ - ft ³	7,61 - 268,31
Dry weight (with standard accessories)	kg - lb	2.500 - 5.500

(a) Chassis type K6. The leght datum refers to model with an external control panel (optional). Please consult for other configurations.



HIMOINSA company with quality certification ISO 9001
 HIMOINSA gensets are compliant with EC mark which includes the following directives:

- ISO 13857:2008 Machinery safety.
- 2006/95/EC Low voltage.
- 89/336/EEC Electromagnetic compatibility.
- 200/14/EC Sound Powr leve. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants. (amended by 2002/88/EC & 2004/26/EC)



Local distributor



Factory: Ctra. Murcia - San Javier, Km. 23,6 30730
 SAN JAVIER (Murcia) España
 Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Export Fax +34968 19 04 20
 info@himoinsa.com www.himoinsa.com